PLUMBING PRODUCTS CONFIGURE-TO-ORDER BOOSTER



PRE-ENGINEERED SYSTEM DESIGNED FOR MINIMIZED COST AND LEAD TIME.
CONFIGURATION TOOL AVAILABLE IN THE GLOBAL PROPOSAL SYSTEM



• APPLICATIONS







Hotels







Shopping Hospitals Centers

Apartment Buildings

Schools

Stadiums



PLUMBING PRODUCTS

CONFIGURE-TO-ORDER BOOSTER





BENEFITS

- Single source responsibility
- Certificate of product liability insurance
- Prefabricated and factory tested
- UL/ C-UL listed packaged pumping system label "QCZJ"
- UL 508A Listed Control Panel with VFD's
- NSF-61 Potable water certification
- NSF-372 certification for weighted average lead content <= 0.25%
- Pipe welding performed by ASME Section IX certified welders
- Structural welding performed by AWS D1.1 certified welders
- TAP Technology control algorithm that meets ASHRAE 90.1 energy efficiency requirements
- Fits through a 36" doorway
- Small footprint and easy installation

STANDARD FEATURES

- Available with vertical multistage and end-suction pumps
- UL 508A Listed Control Panel with HMI touch screen display
- Modbus or BACnet communication for BMS integration
- Piping design and fabrication per ASME B31.1 standard
- Non-Slam, center guided, stainless steel check valve
- Grooved butterfly or threaded ball isolation valves
- AISI 304 Stainless steel piping with a corrosion-resistant polished finish
- Machine grade paint on the structural base
- Multiple monitoring conditions available through the control panel

OPTIONS

- Liquid-filled pressure gauges
- 132 or 185 Gallon, 150 psi rated, ASME Listed, bladder tank with tank feed assembly included
- Reducing couplings for suction and discharge connections
- X-Y multiple points certified test report

CERTIFICATIONS



